

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/102603 A2

(51) International Patent Classification⁷: **H01J 3/00**

(21) International Application Number:
PCT/EP2004/050809

(22) International Filing Date: 14 May 2004 (14.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0311296.8 16 May 2003 (16.05.2003) GB

(71) Applicant (for all designated States except US): **PRINT-ABLE FIELD EMITTERS LIMITED** [GB/GB]; Atlas Centre, Rutherford Appleton Laboratory, Chilton, Didcot Oxfordshire OX11 0QX (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TUCK, Richard, Allan** [GB/GB]; 34 Park Lane, Slough Berkshire SL3 7PF (GB). **WAITE, Michael, Stuart** [GB/GB]; 87 Ashley

Road, Altrincham Cheshire WA14 2LX (GB). **HOWARD, Christopher** [GB/GB]; 32 Aston Street, Oxford Oxfordshire OX4 1EP (GB).


(74) Agent: **STANLEY, David**; Stanleys, Kings Court, 12 King Street, Leeds Yorkshire LS1 2HL (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: FIELD EMITTERS AND DEVICES



(57) Abstract: A broad area field electron emitter comprises a plurality of emitter cells of layered structure. Each cell comprises a hole having a layer of field electron emission material (501) at its base. A gate electrode (503) is spaced from the emitter layer (501) by a dielectric material (502) having a first region in contact with the emitter layer (501) and a second region in contact with the gate electrode (503). The cell diameter is greater at the level of the gate, (503) than at the level of the emitter layer (501), thus enabling electrons in electron beam (505) and emitted from sites adjacent to the side walls of the cell to avoid interception by the gate (503) at point (506). This reduces cell-wall charge between the first and second regions of dielectric material (502), and other means for achieving this are disclosed.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*